

SEA CONTAINER SPECIFICATIONS

www.c-box.co.za

DRY CARGO CONTAINERS



DIMENSIONS

| | Container Weight | | | lı | nterior M | Door Open | | | |
|-------|------------------|--------------|-------------|------------|--------------|-----------|----------------------------|-------|--------|
| Туре | Gross (kg) | Tare (kg) | Net (kg) | Length (m) | Width (m) | Height | Capacity (m ³) | Width | Height |
| 20 ft | 24,000 | 2,370 | 21,630 | 5.898 | 2.352 | 2.394 | 33.20 | 2.343 | 2.280 |
| 40 ft | 30,480 | 4,000 | 26,480 | 12.031 | 2.352 | 2.394 | 67.74 | 2.343 | 2.280 |

CHARACTERISTICS

Manufactured from either Aluminium or steel, they are suitable for most types of cargo / general cargo. Aluminium containers have a slightly larger payload than steel, and steel containers have a slightly larger internal cube

REFRIGERATED CONTAINERS



DIMENSIONS

| | Container Weight | | | li | nterior M | Door Open | | | |
|-------|------------------|--------------|-------------|--------|--------------|-----------|----------------------------|--------------|--------|
| Туре | Gross (kg) | Tare (kg) | Net (kg) | Length | Width (m) | Height | Capacity (m ³) | Width (m) | Height |
| 20 ft | 24,000 | 3,050 | 20,950 | 5.449 | 2.290 | 2.244 | 26.70 | 2.276 | 2.261 |
| 40 ft | 30,480 | 4,520 | 25,960 | 11.690 | 2.250 | 2.247 | 57.10 | 2.280 | 2.205 |

CHARACTERISTICS

Recommended for delicate cargo. Bottom-air delivery system ensures refrigerated cargo reaches its destination in optimum condition.

OPEN TOP CONTAINERS



DIMENSIONS

| | Container Weight | | | l | nterior M | Door Open | | | |
|-------|------------------|--------------|-------------|--------|--------------|-----------|----------------------------|-------|---------------|
| Туре | Gross (kg) | Tare (kg) | Net (kg) | Length | Width (m) | Height | Capacity (m ³) | Width | Height |
| 20 ft | 24,000 | 2,580 | 21,420 | 5.629 | 2.212 | 2.311 | 32.00 | 2.330 | 2.263 |
| 40 ft | 30,480 | 4,290 | 26,190 | 11.763 | 2.212 | 2.311 | 65.40 | 2.330 | 2.263 |

CHARACTERISTICS

Allowing cargo to be loaded from the top, open top containers are particularly suitable for bulky cargo such as machinery. They are fitted with a PVC tarpaulin cover and attachable bows with cable sealing devices. The container doors can be removed to make the stuffing of cargo more convenient. Manufactured from steel

FLAT RACK CONTAINERS



DIMENSIONS

| | Container Weight | | | Interior Measurement | | | | | |
|-------|------------------|--------------|-------------|----------------------|--------------|------------|----------------------------|--|--|
| Туре | Gross (kg) | Tare (kg) | Net (kg) | Length (m) | Width (m) | Height (m) | Capacity (m ³) | | |
| 20 ft | 30,480 | 2,900 | 27,580 | 5.624 | 2.236 | 2.234 | 27.90 | | |
| 40 ft | 34,000 | 5,870 | 28,130 | 11.786 | 2.236 | 1.968 | 51.90 | | |

CHARACTERISTICS

Flatracks are especially suited to heavy loads or cargo that needs loading from the top or sides, such as pipes and machinery. There are collapsible and non-collapsible containers with or without walls. Manufactured from steel.

HIGH CUBE CONTAINERS



DIMENSIONS

| | Container Weight | | | l | nterior M | Door Open | | | |
|-------|------------------|--------------|-------------|--------|--------------|-----------|----------------------------|-------|--------|
| Туре | Gross (kg) | Tare (kg) | Net (kg) | Length | Width (m) | Height | Capacity (m ³) | Width | Height |
| 40 ft | 30,480 | 3,980 | 26,500 | 12.031 | 2.352 | 2.698 | 76.30 | 2.340 | 2.585 |
| 45 ft | 30,480 | 4,800 | 25,680 | 13.544 | 2.352 | 2.698 | 86.00 | 2.340 | 2.585 |

CHARACTERISTICS

With high cube containers, you gain an extra foot in height compared with general-purpose containers. Ideal for light, voluminous cargo or bulky cargo. These extra volume containers come in steel and aluminium.